Vokèra
heating for life

Linea HE

High efficiency combi boiler

SEDBUK 'A' RATED

ENERGY EFFICIENCY RECOMMENDED

4 SEASON FUNCTION

COMPATIBLE WITH ENERGY SAVING CONTROLS

Linea HE
High efficiency combi boiler

SPECIFICATIONS	Linea 28HE	Linea 32HE	Linea 36HE
Central Heating			
Heat input (kW)	25	30	34.6
Maximum heat output @ 60/80 °C (kW)	24.4	29.4	33.7
Maximum heat output @ 30/50 °C (kW)	26.1	31.9	36.7
Domestic Hot Water			
Heat input (kW)	30	34.6	34.6
Flow rate - 35 °C rise (l/min)	12.3	14.2	14.2
Dry weight (kg)	42	44	45
Dimensions			
Height (mm)	845	845	845
Width (mm)	453	453	453
Depth (mm)	358	358	353
Flue Details (concentric)			
Maximum horizontal flue length (60/100mm)	7.8 m	7.8 m	7.8 m
Maximum vertical flue length (60/100mm)	8.8 m	8.8 m	8.8 m
Maximum horizontal flue length (80/125mm)	17.0 m	25.0 m	28.0 m
Maximum vertical flue length (80/125mm)	18.0 m	26.0 m	29.0 m
Flue Details (twin pipes)			
Maximum horizontal flue length (80mm+80mm)	40m+40m	35m+35m	50m+50m
Maximum vertical flue length (80mm+80mm)	40m+40m	35m+35m	50m+50m
Efficiency			
SEDBUK (%)	90.1 (A)	90.3 (A)	90.0 (A)
NOx class	5	5	5

ENERGY SAVING CONTROL OPTIONS

Description	Code
OpenTherm RF Control	611
Wiring kit for use with OpenTherm control	1221179
Weather compensation control	2359259

Further information on these controls can be found in the Vokèra Intelligent controls brochure.

SEDBUK 'A' rated.

Reduces running costs by up to 35% more than a conventional boiler, helping to safeguard the environment.

Low pressure loss reduces noise and increases pump performance.

Adding a Vokèra energy saving control to the Vokèra Linea HE can increase the boilers efficiency by a further 10% so ask your installer about the range of Vokèra energy saving controls.

Low-NOx – highest class-5 performance.

Anti-cycling control prevents energy wasteful on/off cycling and reduces wear and tear.

Minimal appliance heat loss removes the need for compartment ventilation to assist cooling.

Built-in frost protection, protects the appliance from damage during periods of cold weather.

Standard Vokèra pipework layout enables trouble-free replacement of older Vokèra models.

Self-start programming protects the pump and motorised valve from sticking during long periods of inactivity.

Seasonality function with 4-different modes of operation ensures appliance delivers optimum performance and efficiency throughout each season.

Versatile flueing options that can reach lengths up to 50 metres, enabling the boiler to be sited almost anywhere in the home.

Pipe cover supplied as standard.

Can be converted to LPG with LPG Kit.

LINEA HE CONTROL PANEL

A

HHIC HEATING & HOTWATER INDUSTRY COUNCIL

2 YEAR VOKÈRA WARRANTY

GAS safe REGISTER

energy saving recommended

Nox CLASS 5

sbgi

benchmark COLLECTIVE MARK THE MARK OF QUALITY FOR THE INSTALLATION, COMMISSIONING AND SERVICING OF DOMESTIC HEATING AND HOT WATER SYSTEMS

Vokèra is a licensed member of the Benchmark scheme which aims to improve the standards of installation and commissioning of domestic hot water systems in the UK.

Vokèra Ltd Borderlake House, Unit 7 Riverside Industrial Estate, London Colney, AL2 1HG

Email: enquiries@vokera.co.uk **Web:** www.vokera.co.uk **Tel:** 0844 391 0999 **Fax:** 0844 391 0998

Vokèra Ireland West Court, Callan, Co Kilkenny **Tel:** 056 7755057 **Fax:** 056 7755060

Vokèra Limited reserve the right to change specification without prior notice. Consumers statutory rights are not affected. A Riello Group Company.
Company Reg No.: 1047779

Issue1 04/09 cm34