

Unica BHE

High efficiency combi balcony boiler

RANGE 32HE

—
SEDBUK 'A' RATED

—
ALUMINIUM HEAT
EXCHANGER

—
DESIGNED TO
WITHSTAND UK
WEATHER
CONDITIONS



Unica BHE

High efficiency combi balcony boiler

SPECIFICATIONS	Unica 32 BHE
Central Heating	
Heat input (kW)	25
Maximum heat output @ 60/80 °C (kW)	24.45
Maximum heat output @ 30/50 °C (kW)	26.3
Domestic Hot Water	
Heat input (kW)	32
Flow Rate - 35°C rise (l/min)	13.1
Dimensions	
Height	890mm
Width	553mm
Depth	275mm
Weight	
Dry weight (kg)	44
Connections	
Flow & return	22mm
Gas	15mm
DHW hot & cold	15mm
Safety valve	15mm
Condense	21mm
Electrical	
Voltage (V/Hz)	230/50
Flue Details (concentric)	
Maximum horizontal flue length (60/100mm)	7.8m
Maximum vertical flue length (60/100mm)	8.8m
Maximum horizontal flue length (80/125mm)	20m
Maximum vertical flue length (80/125mm)	25m
Flue Details (twin pipes)	
Maximum horizontal flue length (80mm/80mm)	40m/40m
Maximum vertical flue length (80mm/80mm)	40m/40m
Efficiency	
SEDBUK (%)	90.2 (A)
NOx class	5

ENERGY SAVING CONTROLS AND OPTIONS	
Description	Code
REC07 programmable room thermostat	1221169
Weather compensation control	2359259
Security casing (protects against vandalism)	1103289

SEDBUK 'A' rated.

Unique to the market** - designed specifically for external installations, requiring only limited protection to withstand typical UK weather conditions*.

Optional protective security casing available to minimise possible vandalism.

Low NOx - Class-5 performance.

Full IPX5D rating enables the Unica BHE to be installed either on a balcony or on an external wall.

Reduces running costs by up to 35% more than a conventional boiler, helping to safeguard the environment.

Ideal for problematic installations; flats with limited space, if there are difficulties with flue clearances or if a long run to an adequate soak away for the condensate are foreseen.

Designed for easy installation. A pre-fixing jig and built-in filling loop allows the system to be connected and tested without the boiler needing to be in place. Automatic bypass and easy-fit condensate connection.

Simple commissioning, only minimal adjustments are required after installation and automatic modulation eliminates the need to range rate the boiler.

Extremely high modulation ratio, increasing efficiency and component longevity.

Hot water pre-heat provides instant hot water at any time, saving time and energy.

Self-start programming protects the pump and motorised valve from sticking during long periods of inactivity.

Anti-cycling control prevents energy wasteful on/off cycling and reduces wear and tear.

Built-in frost protection, protects the appliance from damage during periods of cold weather.

Intuitive control panel ensures end-users can easily operate and adjust the appliance.

"Autostop" function: Unica BHE has the built-in disabling function (Autostop) that automatically changes the current operating mode, and moves it permanently into the standby mode. This automatic function will only operate after a pre-defined period of time has elapsed and if it has been activated during commissioning.

Versatile flueing options that can reach lengths up to 35 metres.

Built-in thermo-regulation to increase further fuel efficiency. Attach an energy saving control to maximise energy efficiency.

Can be converted to LPG with LPG Kit.

* Some additional protection may be required for extreme weather conditions.



Registered Address: Vokèra Ltd Borderlake House, Unit 7 Riverside Industrial Estate, London Colney, AL2 1HG

Email: enquiries@vokera.co.uk Web: www.vokera.co.uk

Tel: 0844 391 0999

Fax: 0844 391 0998

Vokèra Ireland West Court, Callan, Co Kilkenny

Tel: 056 7755057

Fax: 056 7755060

Vokèra is a licensed member of the Benchmark scheme which aims to improve the standards of installation and commissioning of domestic hot water systems in the UK.