

## **Unica HE** High efficiency combi boiler



RANGE 28HE - 32HE - 36HE

SEDBUK 'A' RATED

ALUMINIUM HEAT EXCHANGER

OPENTHERM TECHNOLOGY



## Unica HE High efficiency combi boiler

SPECIFICATIONS	Unica 28HE	Unica 32HE	Unica 36HE
Central Heating			
Heat input (kW)	20	25	30
Maximum heat output			
@ 60/80 °C (kW)	19.6	24.45	29.31
Maximum heat output			
@ 30/50 °C (kW)	21.0	26.3	31.83
Domestic Hot Water			
Heat input (kW)	28	32	36
Flow Rate - 35°C rise (l/min)	11.5	13.1	14.7
Weight			
Dry weight (kg)	40	42	45
Connections			
Flow & return	22mm	22mm	22mm
Gas	15mm	15mm	15mm
DHW hot & cold	15mm	15mm	15mm
Safety valve	15mm	15mm	15mm
Condense	21mm	21mm	21mm
Electrical			
Voltage (V/Hz)	230/50	230/50	230/50
Flue Details (concentric)			
Maximum horizontal			
flue length (60/100mm)	7.8m	7.8m	7.8m
Maximum vertical			
flue length (60/100mm)	8.8m	8.8m	8.8m
Maximum horizontal			
flue length (80/125mm)	20m	20m	20m
Maximum vertical			
flue length (80/125mm)	25m	25m	25m
Flue Details (twin pipes)			
Maximum horizontal			
flue length (80mm/80mm)	40m/40m	35m/35m	35m/35m
Maximum vertical			
flue length (80mm/80mm)	40m/40m	35m/35m	35m/35m
Efficiency			
SEDBUK (%)	90.5 (A)	90.2 (A)	90.1 (A)
NOx class	5	5	5

## ENERGY SAVING CONTROLS AND OPTIONS

Description	Code
OpenTherm RF Control	611
Weather compensation control	2359259
White pipe cover 400mm/450mm	518/519
Mechanical clock	433

## SEDBUK 'A' rated.

Low NOx - Class-5 performance.

Reduces running costs by up to 35% more than a conventional boiler, helping to safeguard the environment.

Designed for easy installation. A pre-fixing jig and built-in filling loop allows the system to be connected and tested without the boiler needing to be in place. Automatic bypass and easy-fit condense connection as well as standard Vokèra pipework layout enables trouble-free replacement of older Vokèra models.

Simple commissioning, only minimal adjustments are required after installation and automatic modulation eliminates the need to range rate the boiler.

 $\ensuremath{\mathsf{Extremely}}$  high modulation ratio, increasing efficiency and component longevity.

Hot water pre-heat provides instant hot water at any time, saving time and energy.

Self-start programming protects the pump and motorised valve from sticking during long periods of inactivity.

Anti-cycling control prevents energy wasteful on/off cycling and reduces wear and tear.

Integral clock/programmer aperture, enabling direct control over the central heating timings.

Built-in frost protection, protects the appliance from damage during periods of cold weather.

Intuitive control panel ensures end-users can easily operate and adjust the appliance.

"Autostop" function: Unica HE has the built-in disabling function (Autostop) that automatically changes the current operating mode, and moves it permanently into the standby mode. This automatic function will only operate after a pre-defined period of time has elapsed and if it has been activated during commissioning.

Versatile flueing options enable the boiler to be sited almost anywhere in the home.

Built-in thermo-regulation to increase further fuel efficiency. Attach an energy saving control to maximise energy efficiency.

OT+ communication protocol - industry standard method of controls/ communications for remote controls etc.

Fax: 0844 391 0998

Fax: 056 7755060

Can be converted to LPG with LPG Kit.





Vokèra is a licensed member of the Benchmark scheme which aims to improve the standards of installation and commissioning of domestic hot water systems in the UK.

Registered Address: Vokèra Ltd Borderlake House, Unit 7 Riverside Industrial Estate, London Colney, AL2 1HG

Email: enquiries@vokera.co.uk Web: www.vokera.co.uk

Vokèra Ireland West Court, Callan, Co Kilkenny

Tel: 0844 391 0999 Tel: 056 7755057

Vokèra Limited reserve the right to change specification without prior notice. Consumers statutory rights are not affected. A Riello Group Company. Company Reg No.: 1047779